

MR20

Wearable BT UHF Reader

Chainway MR20 is our refined and new generation wearable Bluetooth UHF readers. Being a compact and portable device, it can be operated together with gloves, wristbands, or lanyards and make your work much more flexible and convenient. With a built-in UHF module, Chainway MR20 possesses a powerful data-collection and transmission function via a simple Bluetooth connection with Android/iOS devices. Removable battery and fast charging capability enable it to achieve work continuity for a long duration. Besides, this tiny device has the protection features like dustproof, waterproof, shockproof, and drop resistance. All these functions make the MR20 a most adaptable device in a wide spectrum of circumstances such as logistics & express delivery, retail store management, warehouse management, power patrol inspection, asset management, e-commerce picking, and tickets checking, etc. helping users free their hands and significantly improve work efficiency.



Specification

Physical Characteristics		
Dimensions	50 × 60 × 18 mm / 1.97 × 2.36 × 0.71 in.	
Weight	64 g / 2.26 oz. (with glove: 90 g / 3.17 oz.)	
Color	Yellow, Blue, Gray	
Port	USB Type-C	
Button	ON/OFF, SCAN	
Battery	1000 mAh (removable)	
Charging Current	5 V / 1.5 A	
Charging Duration	1 hours	
LED Indicator	Red indicator will be ON when charging;	
	Blue indicator will be ON when device has been fully charged;	
	Green indicator will be ON when battery is higher than 20%;	
	Green indicator will flash when battery is lower than 20%;	
	Bluetooth is not paired when bluetooth indicator is OFF;	
	Bluetooth is paired when bluetooth indicator is ON	

Performance	
	2

MCU

Cortex-M3 72MHz

Deve	opina	Environment
	9 10 11 19	

SDK	Android / IOS SDK Supported	
Security	RFID Encrypted Module (reserve)	

Communication		
USB Type C	USB connection to realize data transfer	
ВТ	Bluetooth 5.0	

User Environment		
Operating Temp.	-20 °C to +50 °C	
Storage Temp.	-40 °C to +70 °C	
Humidity	5% RH - 95% RH non condensing	
Dropping	1.2 m dropping on concrete	
Sealing	IP65	
UHF		
Engine	CM-Q	
Antenna parameter	Linear Polarized Antenna	
Frequency	920-925 MHz / 902-928 MHz / 865-868 MHz	
Protocol	EPC C1 GEN2 / ISO18000-6C	
R/W range	80 cm	
*Range depends on tags and environment		

Accessories (Optional)

Glove, wristband, lanyard

Notice: Product specifications are subject to change without prior notice. / Model: MR20 / Update Date: 2021-04-26